


FBD 型机械密封

技术参数

非平衡型 Unbalanced
 单端面密封 Single Seal
 任意旋向 Independent on Direction of Rotation
 橡胶波纹管 Elastomer Bellows

介质温度
 介质压力
 线速度

Temperature of Medium: -20°C-150°C
 Pressure of Medium: 0-0.3MPa
 Line Speed: $\leq 10\text{m/sec}$



规格	尺寸					
	d	D	D1	L1	L2	L3
	h6	H8				
FBD-16	16	30	34	8	6	25
FBD-18	18	32	36.8	8	6	25
FBD-20	20	34	38.8	8	6	25
FBD-22	22	35	41.5	8	6	25
FBD-25	25	39	44.8	8	6	26
FBD-28	28	43	48.5	8	6	26
FBD-30	30	48	52	8	7	26
FBD-35	35	53	57	10	8	30
FBD-40	40	58	67	10	8	34
FBD-45	45	63	73	10	8	36
FBD-50	50	68	79	10	8	41
FBD-55	55	73	84	12	10	41
FBD-60	60	79	90	12	10	41
FBD-65	65	86	98.5	12	10	49
FBD-70	70	91	103.5	12	10	52
FBD-75	75	96	110.5	12	10	52
FBD-80	80	105	120	14	12	56
FBD-85	85	110	125	14	12	56
FBD-90	90	115	132	14	12	56
FBD-95	95	120	137	14	12	56
FBD-100	100	125	144	14	12	62
FBD-110	110	135	157	16	14	62
FBD-120	120	145	169	16	14	72